# Certificate of constancy of performance
# 0620-CPR-108636/01

**Issued** *2021-07-01* **Replaces**

**First issued** **Pages** *1 of 2*

CERTIFICATE

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

## Hose reels with semi-rigid hose

whereby the scope of construction product(s) is listed on page 2 of this certificate placed on the market under the name or trademark of

## *CRICO ENGINEERING*

### Zuiddijk 10 - 8340 DAMME

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

## EN671-1:2012

under system 1 for the performances set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product.**

This certificate was first issued on July 1st, 2021 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Ron Scheepers
Kiwa

*Publication of this certificate is allowed.*
*Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.*

562/180812

**Kiwa Nederland B.V.**
Sir Winston Churchilllaan 273
P.O.Box 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Aangewezen instantie Nr. 0620

## Hose reels with semi-rigid hose

### Hose Reel with Semi-rigid hose

| Model | *Disc Diameter (mm)* | Disc Depth (mm) | Hose dimensions | Design |
|---|---|---|---|---|
| CF-HV-20/19 | Ø 600 | 80 | Ø 19 X 20m | Manually operated |
| CF-HV-30/19 | Ø 600 | 100 | Ø 19 x tot 30m | Manually operated |
| CF-HV-20/25 | Ø 600 | 100 | Ø 25 x 20m | Manually operated |
| CF-HV-30/25 | Ø 600 | 150 | Ø 25 x 30m | Manually operated |
| CF-HV7-30/19 | Ø 700 | 60 | Ø 19 x 30m | Manually operated |
| CF-HV7-25/19 | Ø 700 | 60 | Ø 19 x 25m | Manually operated |
| CF-HV7-20/19 | Ø 700 | 60 | Ø 19 x 20m | Manually operated |

The Hose reel have been provided with:
Semi rigid hose at least furbished with the marking:
Hose with a diameter of 19mm: **KIWA – CF – EN694:2014 – A – 2 – 19 – 1,2 (12) – XQ/20XX**
or
Hose with a diameter of 25mm: **KIWA – CF – EN694:2014 – A – 2 – 25 – 1,2 (12) – XQ/20XX**

Stop valve:

For 19mm hose reel, IDC ball valve model: XM20.90.35060 -DN20-KF x KF- without drainage

For 25mm hose reel, IDC ball valve model: XM20.90.45035 -DN25-KF x KF- without drainage

Nozzle model:

For 19mm hose reel, N-09-1 with nominal diameter DN6

For 25mm hose reel, N-09-2 with nominal diameter DN8